



XLR-Adapter, AUX-Klinke 6,35 mm, Mono-Stecker zu XLR-Buchse

- zur Verbindung von XLR-Audio- oder Mikrofonkabel mit z. B. E-Gitarre, E-Klavier, Mischpult, Mikrofon und Lautsprecher mit 6,35-mm-Klinkenbuchse
- Genormte, passgenaue XLR-Buchse
- mit 3-poliger Belegung
- hochwertiges, robustes Metallgehäuse

Anschlüsse:	XLR-Buchse (3-Pin), Klinke 6,35 mm Stecker (2-Pin, mono)
Material Gehäuse:	Zinklegierung, vernickelt
Material Kontakte:	Messing (CuSn6)
Material Steckeinsatz:	PBT 30%
Kontaktwiderstand:	≤ 5 mΩ
Nennstrom:	max. 16 A
Nennspannung:	1000 V ===
Isolationswiderstand:	>2000 MΩ
Dauerhaftigkeit Steckverbindung:	1000x
Einsteck-/Ausziehkraft:	≤ 25 N
Betriebstemperatur:	-30 °C ~ +70 °C

XLR adapter, AUX jack, 6.35 mm mono male to XLR female

- for connecting an XLR audio or microphone cable to e.g. an e-guitar, e-piano, mixer, microphone or speaker with a 6.35 mm jack socket
- standardised, precision-fit XLR socket
- with 3-pin assignment
- high-quality, robust metal housing

Connectors:	XLR female (3-pin), 6.35 mm male (2-pin, mono)
Material housing:	Zinc alloy, nickel-plated
Material contacts:	Brass (CuSn6)
Material plug insert:	PBT 30%
Contact resistance:	≤ 5 mΩ
Rated current:	max. 16 A
Rated voltage:	1000 V ===
Insulation resistance:	>2000 MΩ
Durability of plug connection:	1000x
Insertion/extraction force:	≤ 25 N
Operating temperature:	-30 °C ~ +70 °C

Änderungen

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 03.04.2023	ir	XLR 001, AUX Klinke 6,35mm mono SteckerXLR Buchse	1/1
		gepr.: 03.04.2023	aw		
		Norm:		Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change				27451	

